



TYPICAL PARKING LOT SPACE LAYOUT  
N.T.S.

GENERAL NOTES

1. ALL CONSTRUCTION AND DESIGN METHODS OUTLINED IN NYS DOT SPECIFICATIONS AND STANDARD DETAILS SHALL APPLY.
2. SLOPES OF AT LEAST 2% SHALL BE MAINTAINED TO FACILITATE ADEQUATE DRAINAGE THROUGHOUT PARKING AREA.
3. MAXIMUM SLOPE OF 1.5% SHALL BE MAINTAINED WITHIN PARKING SPACE AREA.
4. MINIMUM NUMBER OF ACCESSIBLE SPACES SHALL CONFORM WITH NYS DOT STANDARD SHEET 608-02.
5. MINIMUM NUMBER OF PARKING SPACES SHALL CONFORM WITH TOWN AND VILLAGE ZONING REQUIREMENTS.
6. ANGLED PARKING SPACES SHALL FOLLOW THE FOLLOWING REQUIREMENTS:
  - 60 DEGREE:
    - WIDTH: 9'-0"
    - LENGTH: 20'-0"
    - AISLE WIDTH: 18'-0"
  - 45 DEGREE:
    - WIDTH: 9'-0"
    - LENGTH: 19'-0"
    - AISLE WIDTH: 16'-0"

STANDARDS

1. NYS DOT SPECIFICATIONS - STANDARD SHEETS
2. ADA REGULATIONS

ISSUE DATE: JANUARY 2019

TOWN & VILLAGE OF ELLICOTTVILLE

DATE

COMMENTS

EVL ENG DEPT.

HIGHWAY - H-10



REVISIONS